

Wall mounted unit

Wall mounted unit, offering good value for money and ensuring a steady supply of clean air

- › Seasonal efficiency values up to A++ in cooling
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › Quiet operation down to 21 dB(A)
- › Choosing for an R-32 product, reduces the environmental impact with 68% compared to R-410A and leads directly to lower energy consumption thanks to its high energy efficiency



Efficiency data		FTXF + RXF		20A + 20A	25A + 25A	35A + 35A	50A + 50A	60A + 60A	
Cooling capacity	Nom.	kW		2.00	2.50	3.50	5.00	6.00	
Heating capacity	Nom.	kW		2.50	3.00	3.50	6.00	6.40	
Power input	Heating	Nom.		kW					
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class		A++					
		Pdesign	kW	2.00	2.50	3.50	5.00	6.00	
		SEER		6.15	6.22	6.21	6.21	6.15	
	Heating (Average climate)	Energy efficiency class		A+					
		Pdesign	kW	2.20	2.40	2.80	4.60	4.80	
		SCOP/A		4.10	4.06				
Nominal efficiency	EER			-					
	COP			-					
Indoor unit		FTXF		20A	25A	35A	50A	60A	
Dimensions	Unit	HeightxWidthxDepth		286x770x225			295x990x263		
Weight	Unit	kg		8.5			13.5		
Air filter	Type	Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High/Super high	m ³ /min	9.9 / 7.8 / 5.8 / 4.8	10.4 / 8.0 / 6.1 / 4.8	11.5/8.3/6.3/4.5	16.8/14.4/11.9/10.5	17.3/14.8/12.2/10.7
		Heating	Silent operation/ Low/Medium/ High/Super high	m ³ /min	10.9 / 8.5 / 6.4 / 5.2	11.1 / 8.5 / 6.7 / 5.2	11.5/9/7/5.3	17.3/14.8/12.2/10.7	17.9/15.8/12.8/11.3
Sound power level	Cooling	dBA		55					
Sound pressure level	Cooling	Silent operation/Low/High/Super high		dBA					
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240					
Outdoor unit		RXF		20A	25A	35A	50A	60A	
Dimensions	Unit	HeightxWidthxDepth		550x658x275			735x825x300		
Weight	Unit	kg		29			31		
Sound power level	Cooling	dBA		60					
Sound pressure level	Cooling	High		dBA					
Operation range	Cooling	Ambient	Min.~Max.	°CDB					
	Heating	Ambient	Min.~Max.	°CWB					
Refrigerant	Type	R-32							
	Charge	kg/TCO ₂ Eq		675					
Piping connections	Liquid	OD	mm		6.35				
	Gas	OD	mm		9.5			12.7	
	Piping length	OU - IU	Max.	m		15			30
	System	Chargeless	m		10				
	Additional refrigerant charge	kg/m		0.02 (for piping length exceeding 10m)					
Level difference	IU - OU	Max.	m		12			20	
Power supply	Phase/Frequency/Voltage	Hz/V		1~/50/220-240					
Current - 50Hz	Maximum fuse amps (MFA)	A		-					

*Note: blue cells contain preliminary data

(1) EER/COP according to Eurovent 2012, for use outside EU only.